

D-SUB Connectors

1 — 2 3 4 5 6 — 7 8 9 10

Specification

> Standard (SDB) D-SUB > High Density (HDB) High Density D-SUB

Number of Contacts

09, 15, 25, 26...78 Contacts
e.g. 09 Pin =(09)

Connector Body (Style)

> For Receptacle (P) Front Fastened > For Overmolded with Cable (A) With Strain Relief > For Field installable (B) Without Strain Relief

Connector (Housing) Gender

(M) Male (F) Female

Contact Gender

(M) Male (Plug) (F) Female (Jack)

Assemble Style

> For Receptacle (S) Solder Type (P) PCB Type (90° / 180°) > For Overmolded with Cable (M) Overmolded with Cable > For Field Installable (A) Field Installable (Solder) (C) Field Installable (Crimped)

Mating Style

(S) Screw Thread (Q) Automated Latch

Backshell

> For Receptacle (With Board Lock) (A) Straight (B) Right Angle (Without Board Lock) (L) Straight (R) Right Angle > For Overmolded with Cable (Without Board Lock) (L) Straight > For Field Installable (Without Board Lock) (L) Straight

Waterproof Rating

(7) IP 67
(8) IP 68

More Information

> For Receptacle (001), (002) Without Cable : Different Versions > For Overmolded with Cable (□)+(■) : Cable Type + Cable Length e.g. (A01) = UL2464 Cable + 1M
□ : Cable Type ■ : Cable Length
(A) UL2464 Cable From 1M to 99M e.g. (01) = 1M