

RBL Connectors



Specification / Current Rating

(SBD) 5A

Number of Contacts

06

EX. (06) = 6 Contacts

Connector Body (Style)

> For Receptacle

> For Overmolded with Cable

> For Field installable

(R) Rear Fastened

(M) With Strain Relief

(F) Without Strain Relief

Connector (Housing) Gender

(M) Male

(F) Female

Contact Gender

(S) Male (Stamp)

(P) Female (Stamp) * Choose the Plating to Tin or Gold.

Assemble Style

> For Receptacle

> For Overmolded with Cable

(S) Solder Type

(C) Crimp Type

> For Field Installable

(C) Crimp Type

Mating Style

(R) Snap-in with

Backshell

> For Receptacle

> For Overmolded with Cable

> For Field

(C) Circular

(L) Straight

Installable

(S) Square Flange

(L) Straight

Waterproof Rating

(7) IP 67

More information

> For Receptacle with Wireharness

> For Overmolded with Cable

(□)+(■) : Wire Type + Wire Length

(□)+(■) : Cable Type + Cable

EX. (A10) = UL1015 Wire + 10 CM

Length

(□) : Wire Type

(■) : Wire Length

(□) : Cable Type

(■) : Cable

(A) UL1015 Wire

(10) 10CM

(A) UL2464 Cable

Length

(30) 30CM

(B) UL2586 Cable

From 1M to 99M

(C) Power Cable(TC-

EX. (01) = 1M

ER)