REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2010/08/10	Aric	Change Rev.01 To Rev.A
B	LEN1490383	2014/09/20	Lu Di	Update Logo
C	C201856	2020/11/25	Vicky	△C *2







Conn.



Pin Assignments

Front View

△C Note:
* QC Important Dimensions To Check
* Waterproof Rate:IP67, Mated
* Housing: Thermoplastic, Black
* Male Pin: Copper Alloy, Gold Plated
* O-Ring: Rubber, Gray
* Lock Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seal B1 For Cable OD:Ø7.5mm~9.5mm
* Seal B2 For Cable OD:Ø4.5mm~7.5mm
* One Set Unassembled In One PE Bag
* UL94V-0 rated materials

UNIT:mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: PWR, 20A, 03P, CABLE W/O SR F, M, FI SOLDER, 2LOCK △C

SCALE 3:2 | SIZE A4 | SHEET 1 OF 1

REV. C | WC-REV. A.5 | QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO PWC-03BFMA-LL7002	DRAWN BY Lu Di	DATE 2014/09/20
DWG NO PWC-03BFMA-LL7002	CHECKED BY Mafei	DATE 2014/09/20
CUSTOMER ALTW	APPROVED BY Jerry	DATE 2014/09/20

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.