REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1160092~095	2011/05/30	Vicky	Modify SR View & Length.
C	LEN1460115~118	2014/06/11	Sam	Modify Logo



Conn.





ALTW
CONFIDENTIAL
2014-06-11
R&D DEPT.

ALTW
DCC. DEPT.
CONFIDENTIAL
2014.06.24
ISSUED

PWCU-04AFFM-LL7AXX

XX:01~99Meters
01:01Meter
02:02Meters
:
:
99:99Meters

Note:
* QC Important Dimension To Check.
* Waterproof Rate:IP67.
* Connector:Nylon+GF,Black.
* Female Pin:Copper Alloy,Gold Plated.
* Lock Nut:Nylon+GF,Black.
* O-Ring:Silicone,Gray.
* Cable:UL2464 16AWG*3C+Drain+Al/Mylar, PVC Jacket,UV Resistant,Black,OD7.5mm.
* Cable Length Tolerance:01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm



Pin Assignments
Front View

Conn.	Wire Color
Pin Out	
4	Black 黑
3	Blue 藍
2	Brown 棕
1	Drain 地線

UNIT:mm

TOLERANCE
±0.5 mm

TITLE: Power,Cable Lock 4Pin F Conn. F Pin (2A+20A)

SCALE 1:1 | SIZE A4 | SHEET 1 OF 1

REV. C | WC-REV. A.1 | QC:Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY Sam	DATE 2014-06-11
DWG NO PWCU-04AFFM-LL7AXX		CHECKED BY Vicky	DATE 2014-06-11
CUSTOMER ALTW		APPROVED BY Rita	DATE 2014-06-11

FMW10702-01-02A1

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.