REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/02/03	Vicky	Initial Released
B	C220642	2022/04/28	Ruru	△B X2
C	C230094	2023/02/02	Vicky	△C X1



AB-CBD XX BR-CBDBR-QF XXX

△B
XX: No. Of Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters



C1 & C2
Pin Assignments
Front View

Pin Out				
C1 & C2	Wire Color			
8	Drain	(26AWG)	地線	
7	Blue	(26AWG)	藍	Twist 對線
6	Red	(26AWG)	紅	
5	Green	(26AWG)	綠	Twist 對線
4	White	(26AWG)	白	
3	Black	(16AWG)	黑	
2	Green	(16AWG)	綠	
1	White	(16AWG)	白	

Note: △B
* RoHS Compliant
* QC Important dimension
△C * Waterproof rate: IP68, mated 1m/24h
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper Alloy, Gold Plated
  O-Ring: Rubber, Gray
  Nut: Thermoplastic, Black
  Outer mold: Thermoplastic, Black
* Cable: UL21996, 16#*3C+(26#*2P+D+AL/MY)+AL/MY, OD=11.0mm, PVC Jacket, Black
* Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm
  1M < L ≤ 3M: +120/-0 mm
  3M < L ≤ 5M: +160/-0 mm
  5M < L ≤ 10M: ±100 mm
  10M < L ≤ 20M: ±200 mm
  20M < L ≤ 30M: ±300 mm
  30M < L ≤ 99M: ±500 mm

UNIT: mm

TOLERANCE
±0.5mm

TITLE: ACC, XLOK, C-10A+5A, DB-ENDED FF

SCALE 33:100 | SIZE A4 | SHEET 1 OF 1

REV. C | WC-REV. A.5 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY Vicky	DATE 2020-02-03
DWG NO AB-CBDXXBR-CBDBR-QFXXX		CHECKED BY Rita	DATE 2020-02-03
CUSTOMER ALTW		APPROVED BY Max	DATE 2020-02-03

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.