








AB-CBD XX ML-CBDBL-QF XXX

 XX: No. Of Pin

XXX: 0.5~99Meters  
A05: 0.5 Meter  
001: 01 Meter  
002: 02 Meters  
:  
099: 99 Meters

Note: 

- \* RoHS Compliant
- \*  Important dimension
- \* C1
-  Waterproof rate: IP68, mated 1m/24h  
Housing: Thermoplastic, Black  
Pin: Copper Alloy, Gold Plated  
Outer mold: Thermoplastic, Black
- \* C2
-  Waterproof rate: IP68, mated 1m/24h  
Housing: Thermoplastic, Black  
Pin: Copper Alloy, Gold Plated  
O-Ring: Rubber, Gray  
Nut: Thermoplastic, Black  
Outer mold: Thermoplastic, Black
- \* Cable: UL21996, 16#\*3C+(26#\*2P+D+AL/MY)+AL/MY,  
OD=11.0mm, PVC Jacket, Black
- \* Cable length tolerance: 0.5M < L ≤ 1M: +60/-0 mm  
1M < L ≤ 3M: +120/-0 mm  
3M < L ≤ 5M: +160/-0 mm  
5M < L ≤ 10M: ±100 mm  
10M < L ≤ 20M: ±200 mm  
20M < L ≤ 30M: ±300 mm  
30M < L ≤ 99M: ±500 mm


UNIT:mm

TITLE  
ACC, XLOK, C-10A+5A, DB-ENDED  
MF

TOLERANCE

SCALE  
33:100SIZE  
A4

SHEET 2 OF 2

REV.  
CWC-REV.  
A.5: Inspection item

**Amphenol LTW**

安費諾亮泰企業股份有限公司

ITEM NO

DRAWN BY

Vicky

DATE

2020-02-03

DWG NO

AB-CBDXXML-CBDBL-QFXXX

CHECKED BY

Rita

DATE

2020-02-03

CUSTOMER

ALTW

APPROVED BY

Max

DATE

2020-02-03