REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2014-01-27	Galaxy	New Item.
B	C190315	2019/03/19	Ruru	Modify Note & Add QC Dimension
C	C240531	2024/05/13	Ruru	△C X2









Pin Assignments
Front View



Recommended Panel
Cut-Out



Note: △B
* QC Important Dimension
* Waterproof Rate: IP67, Unmated
* Housing: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* Use with waterproof cap or dust cap
  Maximum Panel Thickness: 2.3mm
* Use without waterproof cap or dust cap
  Maximum Panel Thickness: 3.5mm
* Gasket and Nut are packed separately
  in PE bags

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: N CERES, ME, B-5A, 02P, REAR FASTENED M, M, SOLDER, 2LOCK △C

SCALE 2:1 | SIZE A4 | SHEET 1 OF 1
REV. C | WC-REV. A.1 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO: IBD-02RMMS-LC7001	DRAWN BY: Ruru	DATE: 2024-05-13
DWG NO: IBD-02RMMS-LC7001	CHECKED BY: Rita	DATE: 2024-05-13
CUSTOMER: ALTW	APPROVED BY: Fred	DATE: 2024-05-13

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.