REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2016/04/26	Spring	Change Rev.01 To Rev.A
B	C190403	2019/03/12	Vicky	Change Note

ALTW
CONFIDENTIAL
2019-03-12
R&D DEPT.











Pin Assignments
Front View



Recommended Panel
Cut-Out

Note:
* QC Important Dimension To Check.
* Waterproof Rate: IP68, Unmated.
  In 1 meter water within 24 hours
* Housing: Thermoplastic, Black.
* Pin: Copper Alloy, Gold Plated.
* Nut: Thermoplastic, Black.
* Gasket: Rubber, Gray.
* Panel Thickness Max: 3.6mm
* Gasket and Nut are packed separately in PE bags.

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: X-Lok D Size Hybrid
3 Male Pin+09 Male Pin

SCALE 3:2 | SIZE A4 | SHEET 1 OF 1
REV. B | WC-REV. A.3 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO: DCD-12RMMS-QC8001	DRAWN BY: Vicky	DATE: 2019-03-12
DWG NO: DCD-12RMMS-QC8001	CHECKED BY: Rita	DATE: 2019-03-12
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2019-03-12

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.