REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2014/01/17	Aric	New Item.
B	C190308	2019/03/20	Ruru	Modify Note & Add QC Dimension
C	C240531	2024/05/20	Ruru	△C X2









Pin Assignments
Front View



Recommended Panel
Cut-Out



Note: △B
* QC Important Dimension
* Waterproof Rate: IP67, Unmated
* Housing: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* Use with waterproof cap or dust cap
  Maximum Panel Thickness:2.3mm
* Use without waterproof cap or dust cap
  Maximum Panel Thickness:3.5mm
* Gasket and Nut are packed separately
  in PE bags

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: N CERES, ME, B-5A, 08P, REAR FASTENED M, M, SOLDER, 2LOCK △C

SCALE 2:1 | SIZE A4 | SHEET 1 OF 1

REV. C | WC-REV. A.2 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
IBD-08RMMS-LC7001	Ruru	2024-05-20
DWG NO	CHECKED BY	DATE
IBD-08RMMS-LC7001	Rita	2024-05-20
CUSTOMER	APPROVED BY	DATE
ALTW	Fred	2024-05-20

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.