

Power Connector PWL Series

Product Specification



1. Scope / 概論

A leading professional solutions provider of waterproof connectors (overmolded with cable, receptacle, field installable) in the industry, Amphenol LTW (ALTW) always fulfills any requirements with high functionality and reliability products; even it is a very special requirement. And it is highly recommended to be applied to harsh environment.

Amphenol LTW (ALTW) 是防水連接器計設及生產的領導者,主要包含線端,板端及現場組裝式連接器以滿足各種使用求及特殊要求,產品具有高效能及高可靠性,非常適合在各種惡劣的環境條件下提供安裝及使用。

This product specification sheet describes the product application in the markets such as Renewable Energy, Industrial

Automation, LED Lighting, Marine, Broadband Wireless Access, Smart Grid, Heavy Equipment, Medical, Electrical Vehicle....etc.

本規範主要描述了 Amphenol LTW(ALTW)產品的應用要求。 本產品廣泛應用於可再生能源，工業自動化，LED，船舶，寬帶無線接入，智能電網，建築機械/重型車輛，醫療設備等，電動車行業....

2. Applicable Documents / 參考文件

2.1 Industry Document / 業界標準

Amphenol LTW (ALTW) 設計及生產的產品符合各項世界標準,包括 IEC, EIA, MIL, NMEA....

3. Specification / 規格

3.1 Material / 材質

Parts / 零件	Material / 材質
Connector / 連接器	Thermoplastic / 熱塑性塑膠
Pin / 端子	Copper Alloy/ 銅合金
Nut / 螺帽	Thermoplastic / 熱塑性塑膠
Clamp Ring / 夾環	Thermoplastic / 熱塑性塑膠
O-Ring / O 型環	Rubber / 橡膠
Gasket / 墊圈	
Seal / 密封圈	
Shield/Shell / 屏蔽	Metal / 金屬

3.2 Rating / 操作評級

Voltage / 電壓	300V Ac/ 300V Dc 300 伏 交流/ 300 伏 直流
Current / 電流	30A 30 安培
Operating Temperature / 操作溫度	-40°C~+105°C 攝式-40 度~105 度
IP / 防水等級	IP67

4. Test Requirement/測試要求

4.1 Appearance/外觀

Item / 項目	Test Condition / 測試條件	Requirement / 條件需求
Examination of product 外觀檢查	EIA-364-18 Visual inspection No physical damage 檢查外觀是否有損壞	No defect would impair normal operation 沒有缺陷會影響正常操作

4.2 Electrical/電氣

Item / 項目	Test Condition / 測試條件	Requirement / 條件需求
Dielectric Withstanding Voltage 耐電壓試驗	EIA 364-20 or IEC 60512-4a AC 1600 voltage for 1 minute, 給予固定 AC 1600V，測試 1 分鐘	The current leakage should be less than 5mA 漏電流需低於 5mA
Contact Resistance 接觸阻抗	EIA-364-23 Mate connectors and measured by dry circuit, 20mV 10mA maximum. 參考 EIA-364-23，公母對插的狀況下，使用 20mV MAX., 10mA.進行量測。	initial : 10 mΩ maximum After test: $\Delta < 10$ mΩ maximum 初始值: 10 mΩ maximum 功能測試后: $\Delta < 10$ mΩ maximum
Insulation Resistance 絕緣電阻	EIA 364-21 Supply DC 500 voltage for 2 minutes. 給予固定 DC 500V, 2 分鐘	The Insulation Resistant should be more than 100MΩ 絕緣阻抗須達 100MΩ 以上
Temperature Rise Test 溫升試驗	UL1977 section 16.1, Mated connector carry the maximum rated current 30A continuously for 4 hour and measure the temperature rise of contact.UL1977 第 16.1 節，配合連接器連續輸入最大額定電流 30A，測試 4 小時，測量接觸溫升	Temperature rise Δt is no more than Relative Thermal Index of the insulating material 溫升 Δt 不大於絕緣材料的相對熱指數

4.3 Mechanical/機械

Item / 項目	Test Condition / 測試條件	Requirement / 條件需求
Durability 耐久性	Test method reference EIA-364-09, at rated cycling of 500±50 per hour 參考 EIA-364-09 進行測試，插拔速率為每小時插拔 500±50 次	500 cycles minimum, no physical damage; Pass the sequenced tests 插拔壽命最小 500 次，無物理損害；符合群組測試
Mating force and Un-mating force 插拔力	EIA-364-13, The connectors shall then be fully mated at a rate of 25.4 millimeters/minute. When without NUT 連接器插拔速率為 25.4mm/分鐘，不含 NUT	<ul style="list-style-type: none"> • Mating Force: 68.6N(7.0kgf) maximum • Un-mating Force: 19.6N(2.0kgf) maximum • 插入力: 最大 68.6N(7.0kgf) • 拔出力: 最大 19.6N(2.0kgf)
Vibration 震動試驗	EIA-364-28, Test condition I, frequency: 10~55~10Hz, amplitude : 1.5 mm; Two hours in each of 3 mutually perpendicular planes. 頻率 : 10~55~10Hz, 振幅: 1.5mm,每軸向測試 2 小時，三個軸向平面均需測試	<ul style="list-style-type: none"> • No physical damages • No electrical discontinuity more than 1μ second. • 無物理損害 • 電氣訊斷不超過 1 μ second
Strain Relief Test 吊重試驗	UL2238 Sec.24 The assembly of a cord to a fitting shall be subjected to a straight pull force as specified for 1 minute. 參考 UL2238 章節 24，以額定的扭力吊重持續 1 分鐘	<ul style="list-style-type: none"> • Wire Size 10 AWG: 178N • Wire Size 12 AWG: 156N • Wire Size 14 AWG: 111N • 線材 10 AWG: 吊重 178N • 線材 12 AWG: 吊重 156N • 線材 14 AWG: 吊重 111N

4.4 Environmental/環境

Item / 項目	Test Condition / 測試條件	Requirement / 條件需求
Mold stress release 模流應力(高溫)試驗	UL 1977 Place in the chamber 115 °C for 7 hours. 參考 UL1977，將試件在溫度 115 °C 的條件下進行烤箱測試 7 小時	<ul style="list-style-type: none"> • No warpage, shrinkage or other distortion that results in uninsulated live part exposed. • 塑膠外殼不得產生扭曲，收縮變型或導體外露之現象。
Thermal Shock 冷熱衝擊試驗	EIA-364-32C, Test condition VIII, 5 cycles at -40°C to +105°C 溫度-40~105°C 共 5 個循環	No physical damages and shall meet requirements of sequenced tests. 無物理損壞，應符合有序測試的要求。
Salt Spray 鹽水噴霧試驗	EIA-364-26, 5% salt solution for 24 hours mated. 5%鹽水溶液持續 24 小時	No physical damages and meets sequenced tests. 無物理損壞
Waterproof Test 防水測試	IEC 60529, IPX7 Should be immersed in water at depth of at least 1 m for 30 minutes. 浸入深度至少 1 米的水中 30 分鐘。	<ul style="list-style-type: none"> • No physical damages • Visual inspection inside no water • Insulation resistance test passed • 無物理損壞 • 目視內部無水侵入 • 絕緣電阻符合規格要求

5. Product Qualification Test Sequence/測試群組及順序

	Test or Examination	Test Group						
		A	B	C	D	E	F	G
		Test Sequence						
Examination of product	Examination of product 外觀檢查	1	1	1, 8	1, 5	1, 5	1	1, 3
Electrical	Contact Resistance 接觸阻抗	2, 6			2, 4	2, 4		
	Dielectric Withstanding Voltage 耐電壓試驗			3				
	Insulation Resistance 絕緣電阻			2, 4, 7				
	Temperature Rise 溫升試驗		2					
Mechanical	Durability 耐久性	4						
	Mating force and Un-mating force 插拔力	3, 5						
	Vibration 振動試驗				3			
	Strain Relief Test 吊重試驗						2	
Environmental	Thermal Shock 冷熱衝擊試驗			5				
	Mold stress release 模流應力(高溫)試驗							2
	Salt Spray 鹽水噴霧試驗					3		
	Waterproof 防水試驗			4, 6				

6. Others/其他

6.1 Torque/扭力

Panel Nut (Receptacle) / 鎖板 (板端)	11.5~14kgf.cm
Panel Screw / 鎖板螺絲 (板端)	4~9 kgf.cm
Clamp Nut / 接管 (組裝式)	10~12 kg.cm
Sealing Nut / 尾蓋 (組裝式)	10~12 kg.cm
Screw of the Screw-in type / 鎖芯線螺絲 (組裝式)	4~9 kgf.cm
Nut plate screw 鎖附壓板	10~12 kg.cm
Other / 其他	/

7. Quality Assurance Provisions/品質保證

Unless otherwise specified, in the contract or purchase order, we will be responsible for the quality of the part as it is delivered to client. We will be responsible for having controlled processes to ensure product is in total compliance with this specification. Failing lots shall be subject to return or other corrective action.

除非在合同或採購訂單中另有規定者外，我們將對交付給客戶的部件質量負責。我們將負責控制流程，以確保產品完全符合規格。未通過的批次應退回或採取其他糾正措施。

Re-qualification Testing : 重新資格測試

If changes significantly affecting form, fit or function are made to the product or manufacturing process, product assurance shall coordinate requalification testing, consisting of all or part of the original testing sequence as determined by development/product, quality and reliability engineering.

如果對產品或製造過程產生顯著影響的形狀，配合或功能的變化，產品保證應協調重新認證測試，包括由開發/產品，質量和可靠性工程確定的全部或部分的原始測試順序。

Our products perform per the specification and criteria described in this document; any usage outside and/or deviating from the specification and criteria described in this document, and/or any alteration, modification, transformation, and application not mentioned in this document must be checked and agreed with ALTW in prior. Failure to check and get our agreement, ALTW will bear no responsibility for any consequence that might arise. It is strongly advised to always check with ALTW for any product application not mentioned in this document and/or applications that need clarifications.

本公司產品之規格及標準，皆依本說明書之說明。對於任何超出或背離本說明書規格範圍之產品使用，或對說明書為提及的任何修改、變更，變造，應用，皆應取得 ALTW 事前的認可，否則 ALTW 對之不負擔任何責任。若對於本說明書說明規格未有規定的事項，或使用上有疑義者，強烈建議先取得 ALTW 之確認及說明。

8. Revision/版本

Document Name		Ceres-A		
Revision	ECN NO.	Description	Date	Sign
01		New Item	2021/02/05	Na Liu