







REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2008/01/28	Yitung	Change REV.01 to REV.A
B	LEN14C0384	2014/12/01	Vicky	Update Logo & Dimension



4	4	4	Brown	棕
3	3	3	Blue	藍
2	2	2	Black	黑
1	1	1	Red	紅
Conn.1	Conn.2	Conn.3	Wire Color	



- Note:
- * \varnothing Important Dimension.
 - * Waterproof Rate: IP66
 - * Connector: Nylon+GF, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Wire Harness: UL1007 24AWG

UNIT:mm		TITLE Standard T Adaptor Lock 4Pin MMM Conn FFF Pin		
TOLERANCE ±0.5 mm				
		SCALE 1:1	SIZE A4	SHEET 1 OF 1
		REV. B	WC-REV. A.2	QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	BA-040404-HHH-TL001	DRAWN BY	Vicky	DATE	2014-12-01
DWG NO	BA-040404-HHH-TL001	CHECKED BY	Sam	DATE	2014-12-01
CUSTOMER	ALTW	APPROVED BY	Rita	DATE	2014-12-01

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.