REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-8B0577	2008/09/10	Shin	Add Note
C	C190274	2019/02/20	Ruru	Modify Note & Change Logo

ALTW
CONFIDENTIAL
2019-02-20
R&D DEPT.









Pin Assignments
Front View



Recommended Panel Cut-Out



Note: C
* QC Important Dimension To Check.
* Waterproof Rate: IP67, Unmated
* Housing: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Black
B * Use with waterproof cap or dust cap
Panel Thickness Max: 4.0mm
B * Use without waterproof cap or dust cap
Panel Thickness Max: 5.0mm
* Gasket and Nut are packed separately in PE bags.

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: Standard, Rear Lock 6P M Conn F Pin
SCALE 1:1 | SIZE A4 | SHEET 1 OF 1
REV. C | WC-REV. A.3 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
BBD-06RMFS-LC7001	Ruru	2019-02-20
DWG NO: BBD-06RMFS-LC7001	CHECKED BY: Rita	DATE: 2019-02-20
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2019-02-20

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.