

1		2		3		4		5		6		7		8			
								REV.		ECN NO.		DATE		SIGN		DESCRIPTION	
								C		LEN-8B0513		2008/09/17		Shin		Add Note	
								D		LEN1730282		2017/03/20		Ruru		Change Logo	
								E		CI90273		2019/02/23		Ruru		Modify Note	

ALTW

CONFIDENTIAL

2019-02-23

R&D DEPT.

5.50

3.18

3.18

1.20*6

6.35

6 Pin Male Connector

Male Pin PCB Layout

ALTW

1

2

3

4

5

6

Pin Assignments

Front View

20.6

23.5(REF.)

ALTW

ALTW

Recommended Panel Cut-out

18.0

4.0

1.8

4.0

15.45 -0.25

20.3

5/8"-27UNS

With Liquid Glue

1

3

2

Connector

Nut

Gasket

Note:

* Important Dimension To Check.

* Waterproof Rate: IP67, Unmated

* Housing: Thermoplastic, Black

* Pin: Copper Alloy, Gold Plated

* Nut: Thermoplastic, Black

* Gasket: Rubber, Black

* Use With Waterproof Cap Or Dust Cap
Panel Thickness Max: 3.0mm

* Use Without Waterproof Cap Or Dust Cap
Panel Thickness Max: 4.0mm

* Gasket and Nut are packed separately in PE bags.

UNIT:mm

.X

.XX

.XXX

ANGLES

±0.25

±0.1

±0.05

±1°

TITLE

Standard

Panel Screw 6Pin M Conn M Pin

SCALE

2:1

SIZE

A4

SHEET

1

OF

1

REV.

E

WC-REV.

A.3

Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

BD-06PMMP-SC7001

DWG NO

BD-06PMMP-SC7001

CUSTOMER

ALTW

DRAWN BY

Ruru

CHECKED BY

Rita

APPROVED BY

Max

DATE

2019-02-23

DATE

2019-02-23

DATE

2019-02-23

8

W10814-03-0001A2