



REV.	ECN NO.	DATE	SIGN	DESCRIPTION




7 Sealing Nut




6 Clamp Ring




5 Seals B2



4 Seals B1





3 Lock Nut



2 Connector





1 O-Ring



Note:

- * Seals B1 for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
(防水墊圈B1線徑: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$)
- * Seals B2 for Cable OD: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$
(防水墊圈B2線徑: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$)
- * One Set Unassembled in One PE Bag
(每一組未組裝, 放置於一個PE袋, 並封口)
- * Important Dimension.
- * Waterproof Rate : IP66
- * Ring: Black, EPDM
- * Housing: Black, Nylon+GF
- * Female Pin: Copper Alloy, Gold Plated
- * Lock Nut: Black, Nylon+GF
- * Seals: Black, EPDM
- * Clamping Ring: Black, Nylon
- * Sealing Nut: Black, Nylon
- * PE Bag: 90mm*85mm

Pin Assignments
Front View 前視圖

UNIT: mm		TOLERANCE		TITLE	
.X	±0.25	Standard, Assy Lock 8Pin F Conn F Pin		SCALE	1:1
.XX	±0.1	SIZE	A4	SHEET	1 OF 1
.XXX	±0.05	REV.	A	WC-REV.	A.2
ANGLES	±1°	QC: Inspection item			

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO.	BD-08BFFA-LL6001	DRAWN BY	SamChang	DATE	2012-03-27
DWG NO.	BD-08BFFA-LL6001	CHECKED BY	Jeffrey	DATE	2012-04-06
CUSTOMER	ALTW	APPROVED BY	Lion	DATE	2012-04-06