ALTW
CONFIDENTIAL
2019-02-25
R&D DEPT.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	LEN-8B0534	2008/09/22	Shin	Add Note
D	LEN1530131	2015/03/16	Jinhai	Change Logo
E	C190269	2019/02/25	Ruru	Modify Note



PCB Lay-out









Pin Assignments
Front View



Recommended Panel Cut-out



Note: E
* QC Important Dimension To Check.
* Waterproof Rate: IP67, Unmated
* Housing: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Black
C * Use With Waterproof Cap Or Dust Cap For Panel Thickness Max: 3.0mm
C * Use Without Waterproof Cap Or Dust Cap For Panel Thickness Max: 4.0mm
* Gasket and Nut are packed separately in PE bags.

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: Standard Panel Screw 10Pin M Conn. M Pin
SCALE: 2:1 | SIZE: A4 | SHEET: 1 OF 1
REV.: E | WC-REV.: A.4 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO: BU-10PMMP-SC7001	DRAWN BY: Ruru	DATE: 2019-02-25
DWG NO: BU-10PMMP-SC7001	CHECKED BY: Rita	DATE: 2019-02-25
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2019-02-25

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.