


Technical drawing of the CD-07BMFM-LL6000 cable assembly. The drawing includes a side view showing the cable length as @CL(mm), a detail of the connector with dimensions @41.8 and @18.0, and a cross-section view of the connector labeled 'Conn.'. A circular stamp from ALTW DCC DEPT. CONFIDENTIAL 2016.05.13 ISSUED is also present.

- * QC Important Dimension To Check.
- * Waterproof Rate: IP66
- * Housing: Nylon+GF,Black
- * Female Pin: Copper Alloy,Gold Plated
- * Cable: UL2464 24AWG*7C+Drain+Al/My,
PVC Jacket UV Resistant, OD=5.8,Black
- * Cable Length Tolerance:01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm



Pin Assignments

Front View

7	White	白
6	Green	綠
5	Brown	棕
4	Red	紅
3	Yellow	黃
2	Orange	橙
1	Blue	藍
Conn.	Wire Color	
	Pin Out	

CD-07BMFM-LL6AXX

XX:01~99Meter
01:01Meter
02:02Meters
:
:
99:99Meters

Cable Length(L):01~99Meters

UNIT:mm		TITLE Middle, Cable Lock 7Pin M Conn. F Pin		<h1>Amphenol LTW</h1> <p>安費諾亮泰企業股份有限公司</p>	ITEM NO	DRAWN BY Ruru	DATE 2016/05/05
TOLERANCE ±0.5 mm		SCALE Free	SHEET 1 OF 1		DWG NO CD-07BMFM-LL6AXX	CHECKED BY Rita	DATE 2016/05/05
		REV. C	SIZE A4		CUSTOMER ALTW	APPROVED BY Lisa	DATE 2016/05/05
		QC :Inspection Item					