REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1610459~462	2016/01/18	Ruru	Change Logo & Note



ALTW
DCC. DEPT.
CONFIDENTIAL
2016.01.29
ISSUED

CDU-14BFMM-SL6AXX

XX:01~99Meters
01:01Meter
02:02Meters
⋮
99:99Meters
Cable Length(L):01~99Meters

Wire Color	Pin Out
Brown/White	14
Black/White	13
Light Green	12
Pink	11
White	10
Gray	9
Purple	8
Blue	7
Green	6
Yellow	5
Orange	4
Red	3
Brown	2
Black	1



Pin Assignments
Front View

ALTW
CONFIDENTIAL
2016.01.18
R&D DEPT.

Note:
* QC Important Dimension.
* Waterproof Rate: IP66
* Housing: Nylon+GF,Black
* Pin: Copper Alloy, Gold Plated
* O-Ring: EPDM, Black
* Nut: Nylon+GF, Black
* Cable: UL2464 24AWG*14C+Drain+AL/My PVC Jacket, UV Resistant, OD=7.0mm, Black
B * Cable Length Tolerance: 01M: ±40mm
02M~05M: ±60mm
06M~10M: ±100mm
11M~30M: ±200mm
31M~99M: ±500mm

UNIT:mm

TOLERANCE: ±0.5mm

TITLE: Middle Cable Screw 14Pin F Conn M Pin

SCALE: Free | SHEET: 1 OF 1

REV: B | SIZE: A4 | QC :Inspection Item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY: Ruru	DATE: 2016/01/18
DWG NO: CDU-14BFMM-SL6AXX		CHECKED BY: Rita	DATE: 2016/01/18
CUSTOMER: ALTW		APPROVED BY: Lisa	DATE: 2016/01/18

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.