






REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	LEN1730319	2017/03/21	Vicky	Update Logo
D	LEN1840067	2018/04/14	Ethan	Modify Panel Thickness
E	CI90314	2019/03/12	Ruru	Modify Note

ALTW  
CONFIDENTIAL  
2019-03-12  
R&D DEPT.

Note:   
\*  Important Dimension  
\* Waterproof Rate: IP67, Unmated  
\* Housing: Thermoplastic, Black  
\* Pin: Copper Alloy, Gold Plated  
\* Nut: Thermoplastic, Black  
\* Gasket: Rubber, Black  
 \* Use Waterproof Cap or Dust Cap  
Panel Thickness Max: 1.8mm  
 \* Use without Waterproof Cap or Dust Cap  
Panel Thickness Max: 3.0mm  
\* Gasket and Nut are packed separately  
in PE bags.

UNIT:mm		TITLE Screw Type Connector For Panel Mount 6Pin Male Connector Male Pin(20A)	
TOLERANCE		SCALE	SHEET OF
.X ±0.25		1:1	A4 1 1
.XX ±0.1		REV.	WC-REV.
.XXX ±0.05		E	A.3
ANGLES ±1°		 Inspection item	

Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO DC-06PMMP-SS7001	DRAWN BY Ruru	DATE 2019-03-12
		DWG NO DC-06PMMP-SS7001	CHECKED BY Rita	DATE 2019-03-12
		CUSTOMER ALTW	APPROVED BY Max	DATE 2019-03-12

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.