| REV. | ECN NO. | DATE | SIGN | DESCRIPTION |
|---|---|---|---|---|
| C | C210219 | 2021/03/16 | Vicky | C X4 |
| D | C210796 | 2021/05/24 | Vicky | D X1 |
| E | C221890 | 2022/12/26 | Vicky | E X1 |




| Pin Out | Pin # | Wire |
|---|---|---|
| | 5 | Green 綠 |
| | 4 | Black 黑 |
| | 3 | Blue 藍 |
| | 2 | White 白 |
| | 1 | Brown 棕 |

Conn.




5P

Pin Assignments
Front View

C 12-XXAMIM-SL7BXX

XX: No. Of Pin

XX: 01~99Meters
01: 01Meter
02: 02Meters
:
:
99: 99Meters
Cable Length(L): 01~99Meters

C Note:
* RoHS Compliant
* QC Important dimension
E * Waterproof rate: IP67, mated
* Connector
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Nut: Metal
Outer mold: Thermoplastic, Black
* Cable: 22#*5C+Insulation, OD=5.0mm,
PU Jacket, Black
B * Cable length tolerance:
1M: +50/−0 mm
1M < L ≤ 3M: +100/−0 mm
3M < L ≤ 5M: +150/−0 mm
5M < L ≤ 10M: ±100 mm
10M < L ≤ 20M: ±200 mm
20M < L ≤ 30M: ±300 mm
D 30M < L ≤ 99M: ±500 mm

| | | | |
|---|---|---|---|
| UNIT: mm | TITLE: O SEN, M12 A (I) B C<br>CABLE W/SR, M, I, MOLDING | ITEM NO | DRAWN BY: Prune / DATE: 2009/01/15 |
| TOLERANCE: ±0.5mm | SCALE: Free / SHEET: 1 OF 1 | DWG NO: C 12-XXAMIM-SL7BXX | CHECKED BY: Tina / DATE: 2009/01/16 |
| | REV: E / SIZE: A4 / QC: Inspection Item | CUSTOMER: ALTW | APPROVED BY: Luke / DATE: 2009/03/25 |

**Amphenol LTW**
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.