


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	LEN1630167~170	2016/03/07	Vicky	Update Logo
E	C210637	2021/05/03	Vicky	△X8
F	C221881	2022/12/07	Vicky	△X1



- △ Note:
- * RoHS Compliant
 - * @ Important dimension
 - △ * Waterproof rate: IP67, mated Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Metal
 - Outer mold: Thermoplastic, Black
 - * Cable: UL2464, PVC Jacket, Black
 - △ * Cable length tolerance:
 - 1M: +50/-0 mm
 - 1M < L ≤ 3M: +100/-0 mm
 - 3M < L ≤ 5M: +150/-0 mm
 - 5M < L ≤ 10M: ±100 mm
 - 10M < L ≤ 20M: ±200 mm
 - 20M < L ≤ 30M: ±300 mm
 - 30M < L ≤ 99M: ±500 mm

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

UNIT: mm	TITLE O SEN, M8 CABLE W/SR, M, M, MOLDING		 Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY	DATE
TOLERANCE ±0.5 mm	SCALE Free	SHEET 1 OF 2		DWG. NO △ 8-XXAMMM-SR7AXX	CHECKED BY Rita	DATE 2016/03/07
	REV. F	SIZE A4	@ : Inspection Item	CUSTOMER ALTW	APPROVED BY Lisa	DATE 2016/03/07



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

4P	5.0	22	8-04AMMM-SR7AXX
3P			8-03AMMM-SR7AXX
△ Contacts	Cable OD	AWG	Item No.


△ 8-XXAMMM-SR7AXX

XX: No. Of Pin

↑
 XX: 01~99Meters
 01: 01Meter
 02: 02Meters
 :
 :
 99: 99Meters
 Cable Length(L): 01~99Meters

Pin Out	4	Black	黑	4	Black	黑
	3	Blue	藍	3	Blue	藍
	1	Brown	棕	2	White	白
				1	Brown	棕
	Pin #	Wire		Pin #	Wire	
Conn.						
		3P			4P	

△ Pin Assignments Front View

UNIT: mm		TITLE	O SEN, M8		△△
TOLERANCE	±0.5 mm	CABLE W/SR, M, M, MOLDING			
SCALE	Free	SHEET	2	OF	2
REV.	F	SIZE	A4	◎ : Inspection Item	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG. NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE
	Vicky	2016/03/07
△ 8-XXAMMM-SR7AXX	Rita	2016/03/07
ALTW	Lisa	2016/03/07