


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	LEN1620149~153	2016/02/01	Ruru	Change Logo
E	C210637	2021/05/03	Vicky	△ X8
F	C221881	2022/12/07	Vicky	△ X1



- △ Note:
- * RoHS Compliant
 - * @C Important dimension
 - △ * Waterproof rate: IP67, mated Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Metal
 - O-Ring: Rubber, Green
 - Outer mold: Thermoplastic, Black
 - * Cable: PU Jacket, Black
 - △ * Cable length tolerance:

1M:	+50/-0 mm
1M < L ≤ 3M:	+100/-0 mm
3M < L ≤ 5M:	+150/-0 mm
5M < L ≤ 10M:	±100 mm
10M < L ≤ 20M:	±200 mm
20M < L ≤ 30M:	±300 mm
30M < L ≤ 99M:	±500 mm

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

UNIT:mm		TITLE	O SEN, M8		ITEM NO	DRAWN BY	DATE
TOLERANCE	±0.5 mm	CABLE W/O SR, F, F, MOLDING	Amphenol LTW		DWG. NO	Ruru	2016/02/01
		SCALE Free	安費諾亮泰企業股份有限公司		△ 8-XXBFFM-SL7BXX	CHECKED BY	DATE
		SHEET 1 OF 1			CUSTOMER	Rita	2016/02/01
		REV. F	SIZE A4	@C : Inspection Item	ALTW	APPROVED BY	DATE
						Lisa	2016/02/01



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

4P	4.8	22	8-04BFFM-SL7BXX
3P	4.5		8-03BFFM-SL7BXX
Contacts	Cable OD	AWG	Item No.

△ 8-XXBFFM-SL7BXX

XX: No. Of Pin

↑
 XX: 01~99Meters
01: 01Meter
02: 02Meters
 :
 :
99: 99Meters
 Cable Length(L): 01~99Meters

Pin Out	4	Black	黑	4	Black	黑
	3	Blue	藍	3	Blue	藍
	1	Brown	棕	2	White	白
				1	Brown	棕
	Pin #	Wire		Pin #	Wire	
Conn.	 <p>△ 3P</p>			 <p>△ 4P</p>		

△ Pin Assignments Front View

UNIT: mm	TITLE O SEN, M8	
TOLERANCE	CABLE W/O SR, F, F, MOLDING	
±0.5 mm	SCALE	SHEET 2 OF 2
	REV. F	SIZE A4
	QC: Inspection Item	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2016/02/01
DWG. NO △ 8-XXBFFM-SL7BXX	CHECKED BY Rita	DATE 2016/02/01
CUSTOMER ALTW	APPROVED BY Lisa	DATE 2016/02/01