




Note:

- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IP68, mated 1m/24h IP69K, mated
- * Connector
- * Housing: Thermoplastic, Black
- * Pin: Copper alloy, Gold plated
- * Nut: Metal
- * Outer mold: Thermoplastic, Black
- * Cable: UL2517, PVC Jacket, Black
- * Cable length tolerance: 1M: +50/-0 mm

1M < L ≤ 3M:	+100/-0 mm
3M < L ≤ 5M:	+150/-0 mm
5M < L ≤ 10M:	±100 mm
10M < L ≤ 20M:	±200 mm
20M < L ≤ 30M:	±300 mm
30M < L ≤ 99M:	±500 mm


```
- XX:01~99Meters
  01:01Meter
  02:02Meters
  :
  99:99Meters
```

C	Pin Out	5 -- 4 Black 黑 3 Blue 藍 2 -- 1 Brown 棕	5 -- 4 Black 黑 3 Blue 藍 2 White 白 1 Brown 棕	5 Gray 灰 4 Black 黑 3 Blue 藍 2 White 白 1 Brown 棕
		Pin # Wire	Pin # Wire	Pin # Wire
B	Conn.			
		3P	4P	5P

Pin Assignments Front View

A	UNIT: mm		TITLE N SEN, M12 D, SCREW CABLE W/O SR, M, M, MOLDING		
	TOLERANCE ±0.5mm		SCALE 3:2	SIZE A4	SHEET 2 OF 2
			REV. F	WC-REV. A.2	: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Yulong-wang	2016-10-14
DWG NO	CHECKED BY	DATE
 M12D-XXBMMM-SR8DXX	Jinhai	2016-10-14
CUSTOMER	APPROVED BY	DATE
ALTW	Jerry	2016-10-14