REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C		2020/04/17	JC Chen	△C X2
D	C210561	2021/04/14	Vicky	△D X3
E	C230009	2023/01/03	Vicky	△E X1







△C △D
MSAP-XXBFFA-SR7001
XX: No. Of Pin

△C △D
Note:
* RoHS Compliant
* (QC) Important Dimension
△E * Waterproof rate: IP67, mated
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Extension Nut: Thermoplastic, Black
  Nut: Thermoplastic, Black
  O-Ring: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
△B * Seal: Rubber, Gray, OD:Ø4.0mm~Ø7.0mm
* One set unassembled in one pe bag



Pin Assignments Front View

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: N SEN, MI2 A -PLASTIC, SCREW △D CABLE W/O SR, F, F, FI SOLDER
SCALE: 1:1 | SIZE: A4 | SHEET: 1 OF 1
REV.: E | WC-REV.: .0 | (QC): Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY: Yulong_wang	DATE: 2016-07-22
DWG NO: MSAP-XXBFFA-SR7001	CHECKED BY: Jinhai	DATE: 2016-07-22
CUSTOMER: ALTW	APPROVED BY: Jerry	DATE: 2016-07-22

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.