REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C210561	2021/04/19	Vicky	△B X3
C	C221953	2022/12/16	Ruru	△C X1

△B MSDP-XXBMMA-SL8001

XX: No. Of Pin







Pin Assignments Front View

△B Note:
* RoHS Compliant
* (QC) Important Dimension
△C * Waterproof rate: IP68, mated 1m/24h
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Extension Nut: Thermoplastic, Black
  Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seal: Rubber, Gray, OD:Ø4.5mm~Ø6.5mm
* One set unassembled in one pe bag

UNIT:mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

△B

TITLE: N SEN, M12 D -PLASTIC, SCREW CABLE W/O SR, M, M, FI SOLDER △B

SCALE: 1:1 | SIZE: A4 | SHEET: 1 OF 1 | REV.: C | WC-REV.: A.5

(QC): Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY: JC Chen	DATE: 2019-08-28
DWG NO: MSDP-XXBMMA-SL8001		CHECKED BY: Li Feng	DATE: 2019-08-28
CUSTOMER: ALTW		APPROVED BY: Jerry	DATE: 2019-08-28

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.