REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C201548	2020/10/12	Vicky	△B X4
C	C210561	2021/04/19	Vicky	△C X3
D	C221877	2022/12/13	Ruru	△D X1

△B MSDP-XXBMMB-SR7001

XX: No. Of Pin









4P

Pin Assignments
Front View

△B △C
Note:
* RoHS Compliant
* (QC)Important Dimension
△D * Waterproof rate: IP67, mated
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Extension Nut: Thermoplastic, Black
  Nut: Thermoplastic, Black
  O-Ring: Rubber, Gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seal: Rubber, Gray, OD:Ø4.0mm~Ø7.0mm
* One set unassembled in one pe bag

UNIT:mm

TOLERANCE △C

.X	±0.25
.XX	±0.1
.XXX	±0.05
ANGLES	±1°

TITLE: N SEN, M12 D -PLASTIC, SCREW CABLE W/O SR, M, M, FI SCREWIN △B △C

SCALE	SIZE	SHEET	OF
1:1	A4	1	1

REV. D | WC-REV. A.1 | (QC):Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY: Mila	DATE: 2015-10-13
DWG NO: △B MSDP-XXBMMB-SR7001	CHECKED BY: Cary	DATE: 2015-10-13
CUSTOMER: ALTW	APPROVED BY: Jerry	DATE: 2015-10-13

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.