



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
E	C210084	2021/01/18	Vicky	△E X1
F	C210211	2021/03/22	Ruru	△F X2
G	C222007	2022/12/27	Ruru	△G X1

△D
MSDS-XXBFFM-SL8BXX
XX: No. Of Pin
XX:01~99Meters
01:01Meter
02:02Meters
⋮
99:99Meters



Conn.

Pin Out	Shield	Braid
4	Black	黑
3	Blue	藍
2	White	白
1	Brown	棕
Pin #	Wire	



Pin Assignments Front View

- Note: △D △F
 * RoHS Compliant
 * ◎◎ Important dimension
 △G Waterproof rate: IP68, mated 1m/24h
 IP69K, mated
- * Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - △E O-Ring: Rubber, Gray
 - Nut: Metal
 - Shield: Metal
 - Outer mold: Thermoplastic, Black
 - * Cable: UL20549, Shield, 22#*4C+AL/MY+B, OD=5.3, PU Jacket, Black
 - * Cable length tolerance:
 - 1M < L ≤ 3M: +50/-0 mm
 - 3M < L ≤ 5M: +100/-0 mm
 - 5M < L ≤ 10M: ±100 mm
 - 10M < L ≤ 20M: ±200 mm
 - 20M < L ≤ 30M: ±300 mm
 - 30M < L ≤ 99M: ±500 mm

UNIT:mm		
TOLERANCE		
±0.5mm		

TITLE N SEN, M12 D -SHLD, SCREW CABLE W/O SR, F, F, MOLDING △F			
SCALE 3:2	SIZE A4	SHEET 1 OF 1	
REV. G	WC-REV. A.3	◎◎: Inspection item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Brady	DATE 2019/03/05
DWG NO △D MSDS-XXBFFM-SL8BXX	CHECKED BY Eagle	DATE 2019/03/05
CUSTOMER ALTW	APPROVED BY Neo	DATE 2019/03/05