



REV. B	ECN NO. LEN1720090~093	DATE 2017/02/09	SIGN Ruru	DESCRIPTION Change Logo & Outer Mold Design & Note
--------	------------------------	-----------------	-----------	--

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.




PB-040400-MM0-TSAXX

XX:01~99Meter  
 01:01Meter  
 02:02Meters  
 :  
 :  
 99:99Meters

Cable Length(L):01~99Meters

- Note:
- \*  $\text{\textcircled{C}}$  Important Dimension.
  - \* Waterproof Rate: IP68
  - \* Housing: Black, Polyurethane
  - \* Screw Nut: Black, Nylon+GF
  - \* Male Pin: Copper Alloy, Gold Plated
  - \* Wire Harness: UL1007 24AWG, 4Pcs
  - \* Cable: UL2464 22AWG\*4C+Talc  
Black, PVC Jacket UV Resistant OD=5.0mm
  - \*  $\text{\textcircled{A}}$  Cable Length Tolerance: 01M:  $\pm 40\text{mm}$   
02M~05M:  $\pm 60\text{mm}$   
06M~10M:  $\pm 100\text{mm}$   
11M~30M:  $\pm 200\text{mm}$   
31M~99M:  $\pm 500\text{mm}$



Conn.1&2  
Pin Assignments  
Front View

4	Black	黑	4
3	Blue	藍	3
2	White	白	2
1	Brown	棕	1
Conn.1	Wire Color		Conn.2
Pin Out			

UNIT:mm	
TOLERANCE	$\pm 0.5 \text{ mm}$

TITLE		M12P B Coded Conn	
T Cable Screw MM Conn MM Pin			
SCALE	Free	SHEET	1 OF 1
REV. B	SIZE A4	$\text{\textcircled{C}}$ :Inspection Item	

**Amphenol LTW**  
安費諾亮泰企業股份有限公司

ITEM NO	
DWG NO	PB-040400-MM0-TSAXX
CUSTOMER	ALTW

DRAWN BY	Ruru
CHECKED BY	Rita
APPROVED BY	Max

DATE	2017/02/09
DATE	2017/02/09
DATE	2017/02/09