



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF AMPHENOL LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY AMPHENOL LTW.



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2023/01/19	Roy Lin	Rev.01 to Rev.A



Type A 金屬外殼結合縫外觀樣式非QC重點，請忽略，
Type A 除此部分，外觀尺寸大小皆須符合圖面



Shield	Braid	編織	Shield
9	Blue	藍	B11
8	White	白	B10
7	Drain	地線	B12
			B1
			A12
			A1
			B12
6	Blue	藍	B1
			A12
			A1
5	White	白	A2
4	Drain	地線	A3
			B12
			B1
			A12
3	Green	綠	A1
			A2
			A3
			B12
2	White	白	B1
1	Red	紅	A7
			A6
			B4
			A9
C2	Wire Color		A4
Pin Out			C1



UC30ML-NAML-QBXXX
XXX: 01~02Meters
001: 01Meter
002: 02Meters

Note:
* \varnothing Important Dimension
* C1
Waterproof Rate: IP68, Mated 1m/24h
Connector: USB Type C, Plug
Housing: Thermoplastic, UL94 V-0, Black
Gasket: Rubber, Black
* C2
Waterproof Rate: Non-waterproof.
Connector: USB Type A 3.0, Plug
* Other
Cable: (USB3.1) UL2725 (32#*IP+EAM)*2C+(32#*IP+AL)*1C+
26#*2C+AB, OD=4.0mm, PVC Jacket, Black

UNIT:mm		TITLE
TOLERANCE	± 0.5 mm	ACC, USB, C TYPE, DB-ENDED, MM
SCALE	1:1	SIZE A4
REV.	A	SHEET 1 OF 1
WC-REV.	.0	QC: Inspection item

Amphenol LTW		ITEM NO	UC30ML-NAML-QBXXX	DRAWN BY	Roy Lin	DATE	2023-01-19
安費諾亮泰企業股份有限公司		DWG NO	UC30ML-NAML-QBXXX	CHECKED BY	Victor Hung	DATE	2023-01-19
		CUSTOMER	ALTW	APPROVED BY	Max Yang	DATE	2023-01-19