





THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2018/04/16	Brady	New Initial
B	C230039	2023/01/10	Jiahe Lin	$\triangle B$ *3
C	C240352	2024/01/02	Hubert	$\triangle C$ X2


$\triangle C$ MSDS-XXBMMM-SL8EXX

XX: No. Of Pin

XX:01~99Meters
 01:01Meter
 02:02Meters
 :
 99:99Meters



- Note:
- * RoHS Compliant
 - * \varnothing Important dimension
 - * Waterproof rate: IP68, mated 1m/24h, IP69K mated
 - * Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Metal
 - Outer mold: Thermoplastic, Black
 - * Cable: CAT-5E, 24#*2P+AL/MY+B+F, OD=6.4mm, TPU Jacket, Blue
 - * Cable length tolerance: 1M: +50/-0 mm
 - 1M < L ≤ 3M: +100/-0 mm
 - 3M < L ≤ 5M: +150/-0 mm
 - 5M < L ≤ 10M: ±100 mm
 - 10M < L ≤ 20M: ±200 mm
 - 20M < L ≤ 30M: ±300 mm
 - 30M < L ≤ 99M: ±500 mm



4P

Pin Assignments
Front View

Shield	Braid	編織	
4	Green	綠	Twist
2	White/Green	白/綠	
3	Orange	橘	Twist
1	White/Orange	白/橘	
Connector	Wire Color		Pin Out

UNIT:mm		
TOLERANCE	±0.5mm	

TITLE N SEN, M12 D -SHLD, SCREW CABLE W/O SR, M, M, MOLDING $\triangle C$			
SCALE 3:2	SIZE A4	SHEET 1 OF 1	
REV. C	WC-REV. A.2	\varnothing : Inspection item	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO $\triangle B$	DRAWN BY Hubert	DATE 2024/04/02
DWG NO MSDS-XXBMMM-SL8EXX	CHECKED BY Aric	DATE 2024/04/02
CUSTOMER ALTW	APPROVED BY Fred	DATE 2024/04/02