

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



F

E

D

C

B

A

CB-XXAMFM-RR7A XX

Middle Size Current Rating 10A

XX:No. Of Pin(Pin 數)

A:Cable With S/R(線端帶網尾)

M:Male Connector(公座)

F:Female Pin(母Pin)

M:Molding Type(射出成型)


XX:01~99Meter
01:01Meter
02:02Meter
:
99:99Meter




A:UL 2464 Cable

7:IP67(防水等級 67)

R:Right Angle(90°)

R:Snap In With Latch(彈臂卡合式)



Pin Out	4 -- 3 Red 紅 2 -- 1 Black 黑	4 Green 綠 3 White 白 2 -- 1 Black 黑	4 Orange 橙 3 Red 紅 2 Brown 棕 1 Black 黑
Pin Assignments Front View	 2Pin	 3Pin	 4Pin

UNIT:mm			TITLE MLDDIE CABLE RBL M CONN F PIN		ITEM NO	DRAWN BY Mafei	DATE 2016/08/08
TOLERANCE ±0.5			SCALE 1:1	SIZE A4	DWG NO CB-XXAMFM-RR7AXX	CHECKED BY Joyy	DATE 2016/08/08
			REV. C	WC-REV. A.2	CUSTOMER ALTW	APPROVED BY Jerry	DATE 2016/08/08
			QC:Inspection item				

Amphenol LTW
安費諾亮泰企業股份有限公司