



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



CB-XXAMMM-RL7A XX

Middle Size Current Rating 10A

XX:No. Of Pin (Pin 數)

A:Cable With S/R (線端帶網尾)

M:Male Connector (公座)

M:Male Pin (公Pin)

M:Molding Type (射出成型)

XX:01~99Meter

01:01Meter

02:02Meter

...


99:99Meter

A:UL 2464 Cable

7:IP67 (防水等級 67)

L:Straight (180°)

R:Snap In With Latch (彈臂卡合式)




Pin Out

4 --  
3 Red 紅  
2 --  
1 Black 黑


4 Green 綠  
3 White 白  
2 --  
1 Black 黑

4 Orange 橙  
3 Red 紅  
2 Brown 棕  
1 Black 黑


Pin  
Assignments  
Front View



2Pin




3Pin



4Pin

UNIT:mm



TOLERANCE  
±0.5

TITLE

MIDDLE  
CABLE RBL M CONN M PIN

SCALE 3:4

SIZE A4

SHEET 2 OF 2

REV. D

WC-REV. A.3

QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

DWG NO

CB-XXAMMM-RL7AXX

CUSTOMER

ALTW

DRAWN BY

Mafei

CHECKED BY

Jerry

APPROVED BY

Max

DATE

2017-03-27

DATE

2017-03-27

DATE

2017-03-27