



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



F

E

D

C

B

A

CB-XXAFMM-RL7A XX

Middle Size Current Rating 10A

XX:No. Of Pin(Pin 數)

A:Cable With S/R(線端帶網尾)

F:Female Connector(母座)

M:Male Pin(公Pin)

M:Molding Type(射出成型)


XX:01~99Meter  
01:01Meter  
02:02Meter  
:  
99:99Meter




A:UL 2464 Cable


7:IP67(防水等級 67)

L:Straight(180°)

R:Snap In With Latch(彈臂卡合式)



Pin Out	4 -- 3 Red 紅 2 -- 1 Black 黑	4 Green 綠 3 White 白 2 -- 1 Black 黑	4 Orange 橙 3 Red 紅 2 Brown 棕 1 Black 黑
Pin Assignments Front View	 2Pin	 3Pin	 4Pin

UNIT:mm				TITLE MIDDLE CABLE RBL F CONN M PIN		Amphenol LTW  安費諾亮泰企業股份有限公司		ITEM NO		DRAWN BY Mafei		DATE 2016/08/08							
TOLERANCE ±0.5								SCALE 3:4		SIZE A4		SHEET 2 OF 2		DWG NO CB-XXAFMM-RL7AXX		CHECKED BY Joyy		DATE 2016/08/08	
								REV. C		WC-REV. A.3		QC:Inspection item		CUSTOMER ALTW		APPROVED BY Jerry		DATE 2016/08/08	
1		2		3		4		5		6		7		8 FMM10702-01-02A1					