REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C231273	2023/10/06	Ruru	B X5

B
ABB-XXBFMC-SL7XP0

XX: No. Of Pin

A: With Red&Yellow&Blue Color Seal
S: With Red Color Seal, Cable OD 5.0~6.0mm.
M: With Yellow Color Seal, Cable OD 6.0~8.0mm.
L: With Blue Color Seal, Cable OD 8.0~10.0mm.









2P 3P

Pin Assignments Front View

B Note:
* RoHS Compliant
* QC Important dimension
* Waterproof rate: IP67, mated
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Nut: Thermoplastic, Black
  O-Ring-1: Rubber, Gray
  O-Ring-2: Rubber, Dark gray
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Sealing : Rubber
* One set unassembled in one pe bag

UNIT: mm

TOLERANCE
±0.5 mm

TITLE: N CERES, ST, B-10A, CABLE W/O SR F, M, CRIMP, SCREW B

SCALE 8:5 | SIZE A4 | SHEET 1 OF 1 B

REV. B | WC-REV. A.3 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Peng	2018-08-06
DWG NO: B ABB-XXBFMC-SL7XP0	CHECKED BY: Mafei	DATE: 2018-08-06
CUSTOMER: ALTW	APPROVED BY: Jerry	DATE: 2018-08-06

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.