REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	C191760	2019/10/15	Jane	△C X5
D	C192018	2019/11/15	Vicky	△D X4
E	C231240	2023/09/22	Ruru	△E X2







△E BB-XXBMFA-QL8XNP

XX: No. Of Pin

S: With Red Color Seal 1, Cable OD 5.0~6.0mm.
M: With Yellow Color Seal 2, Cable OD 6.0~8.0mm.
L: With Blue Color Seal 3, Cable OD 8.0~10.0mm.
A: With Seal 1 & Seal 2 & Seal 3.

Pin Assignments Front View



2 Pin

3 Pin

△D Note:
* QC Important Dimension
* Waterproof Rate: IP68, mated 1m/24h
* Housing: Thermoplastic, Black
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
* Seals: Rubber
△E * One set unassembled in one pe bag

UNIT: mm

TOLERANCE ±0.5mm

TITLE: XLOK, B-10A, CABLE W/O SR M, F, FI CRIMP, XLOK △D

SCALE 1:1 | SIZE A4 | SHEET 1 OF 1

REV. E | WC-REV. A.5 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Brady Chung	2019-09-24
DWG NO: BB-XXBMFA-QL8XNP △D	CHECKED BY: Jane Wang	DATE: 2019-09-24
CUSTOMER: ALTW	APPROVED BY: Neo Tsai	DATE: 2019-09-24

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.