REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LENI350056	2013/04/24	Ruru	Modify Cable OD Max
C	LENI5B0043	2015/10/27	Ruru	Change Logo
D	C231272	2023/10/03	Vicky	△D X2





Note:
* (QC) Important Dimension To Check.
* Waterproof Rate: IP67
* Connector: Nylon+GF, Black
* Pin: Copper Alloy, Gold Plated
* Clamp Ring: Nylon, Black
* Seal: EPDM, Black
* Sealing Nut: Nylon, Black
△B △D * Cable OD Max : ∅10.0~∅12.4mm
△D * One set unassembled in one pe bag

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: O CERES, D-20A+5A, 12P, CABLE W/O SR M, M PWR+F SIG, FI SOLDER, 2LOCK △D

SCALE 1:1 | SIZE A4 | SHEET 1 OF 1

REV. D | WC-REV. B.2 | (QC): Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DCD-12BMEA-LL7001	Ruru	2015-10-27
DWG NO: DCD-12BMEA-LL7001	CHECKED BY: Rita	DATE: 2015-10-27
CUSTOMER: ALTW	APPROVED BY: Lisa	DATE: 2015-10-27

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.