REV.	ECN NO.	DATE	SIGN	DESCRIPTION
F	C210309	2021/02/26	Ruru	F X2
G	C221973	2022/12/22	Ruru	G X1
H	C231034	2023/08/09	Ruru	H X1



Recommended Panel Cut-Out

B

D
MI2B-XXPMMS-SH8001

XX: No. Of Pin











3P



4P



5P

Pin Assignment Front View

C

D F Note:
* RoHS Compliant
* QC Important dimension
G C * Waterproof rate: IP68, unmated 1m/24h
H IP69K, mated
* Connector
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
F * Shield: Metal
E * Nut: Metal
* O-Ring: Rubber, Black
* For panel thickness max: 4.5mm
* Nut is packed separately in pe bag

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: N SEN, MI2 B, SCREW RECEPTACLE, M, M, SOLDER F

SCALE 3:2 | SIZE A4 | SHEET 1 OF 1
REV. H | WC-REV. A.5 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY: Yulong_wang	DATE: 2016-09-05
D MI2B-XXPMMS-SH8001	CHECKED BY: Jinhai	DATE: 2016-09-05
CUSTOMER: ALTW	APPROVED BY: Jerry	DATE: 2016-09-05

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.