REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	C220644	2022/04/28	Ruru	△C X4
D	C230086	2023/01/31	Ruru	△D X1
E	C240009	2024/01/03	Arvin Chan	△E X1

△C
BBD-XXRMFS-QC8001

XX: No. Of Pin







△E



4P



6P

Pin Assignment
Front View



Recommended
Panel Cut-out



Note: △B △C
* RoHS Compliant
* QC Important dimension
△D * Waterproof rate: IP68, unmated 1m/24h
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* For panel thickness max: 4.5mm
* Gasket and nut are packed separately in pe bag

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: XLOK, B-10A+5A, REAR FASTENED M, F, SOLDER, PUSH LOCK △C

SCALE	SIZE	SHEET
2:1	A4	1 OF 1
REV. E	WC-REV. A.3	QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Arvin Chan	2024-01-03
DWG NO: BBD-XXRMFS-QC8001 △C	CHECKED BY: Fisher Wang	DATE: 2024-01-03
CUSTOMER: ALTW	APPROVED BY: Fred Lee	DATE: 2024-01-03

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.