

	1	2	3	4	5	6	7	8		
F	M5-XXBMMM-SL7FXX XX:NO.OF Pin XX:01~99Meter 01:01Meter 02:02Meters : 99:99Meters				REV.	ECN NO.	DATE	SIGN	DESCRIPTION	
					A	-	2021/10/20	Allen	New Initial.	
					B	C211672	2021/11/03	Allen	<div>△B</div> X3	
					C	C221876	2022/12/08	Ruru	<div>△C</div> X2	
E	<div>5.0</div>				<div>⌀ L (mm)</div> <div>30.0</div> <div>⌀6.4</div>					
D					<div>△B M5*0.5</div>					
C	3Pin		4Pin		<div>Note</div> <div>* ⌀ Important Dimension To Check</div> <div>* Waterproof Rate: IP67, Mated.</div> <div>* Connector</div> <div>Housing: Thermoplastic, Black.</div> <div>Pin: Copper Alloy, Gold Plated.</div> <div>Nut: Metal.</div> <div>Outer mold: Thermoplastic, Black.</div> <div>* Cable: UL2103 26AWG, PVC Jacket, Black.</div> <div>* Cable length tolerance: 1M: +50/-0 mm</div> <div>1M < L ≤ 3M: +100/-0 mm</div> <div>3M < L ≤ 5M: +150/-0 mm</div> <div>5M < L ≤ 10M: ±100 mm</div> <div>10M < L ≤ 20M: ±200 mm</div> <div>20M < L ≤ 30M: ±300 mm</div> <div>30M < L ≤ 99M: ±500 mm</div> <div>* RoHS Compliant.</div>					
	4 Black 黑	4 Black 黑	3 Blue 藍	3 Blue 藍						
	1 Brown 棕	2 White 白	1 Brown 棕	2 White 白						
	Pin #	Wire	Pin #	Wire						
B	Pin Out									
	Pin Assignments Front View									
A	UNIT:mm				TITLE		ITEM NO		DRAWN BY	DATE
	TOLERANCE	±0.5mm			N SEN, M5, SCREW CABLE W/O SR, M, M, MOLDING <div>△C</div>		M5-XXBMMM-SL7FXX		Allen	2021/10/20
	SCALE 3:1		SIZE A4	SHEET 1 OF 1	DWG NO		CHECKED BY		Wen	2021/10/20
	REV. C		WC-REV. .0	⌀: Inspection item		CUSTOMER		APPROVED BY	Neo	2021/10/20
					ALTW					
	1	2	3	4	5	6	7	8	W10814-03-0001A2	