



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
E	C190405	2019/03/15	Ruru	Modify Note
F	C220799	2022/05/26	Vicky	\triangle FX2
G	C231529	2023/12/08	Lavy	\triangle GX3

- \triangle \triangle F Note:
- * RoHS Compliant
 - * \textcircled{DD} Important dimension
 - \triangle G * Waterproof rate: IP67, mated Connector
 - Housing: Thermoplastic, Black, RJ45 jack, shielded
 - * Nut: Thermoplastic, Black
 - * Gasket: Rubber, Gray
 - * Use with waterproof cap or dust cap
Panel thickness max: 1.8mm
 - * Use without waterproof cap or dust cap
Panel thickness max: 3.0mm
 - * Gasket and nut are packed separately in pe bag

UNIT:mm		TITLE	
TOLERANCE		RJ, C PLASTIC, C5E SHLD	
.X	± 0.25	FRONT FASTENED, F, PNL JACK R, 3LOCK	
.XX	± 0.1	SCALE	1:1
.XXX	± 0.05	SIZE	A4
ANGLES	$\pm 1^\circ$	SHEET	1 OF 1
REV.	G	WC-REV.	B.4
		\textcircled{DD} : Inspection item	

Amphenol LTW		ITEM NO	RCP-5SPFFV-TCM7001	DRAWN BY	Lavy	DATE	2023-12-08
安費諾亮泰企業股份有限公司		DWG NO	RCP-5SPFFV-TCM7001	CHECKED BY	Jerry	DATE	2023-12-08
		CUSTOMER	ALTW	APPROVED BY	Fred	DATE	2023-12-08

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.