

















THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

	1	2	3	4	5	6	7	8				
F												
E	FLBC- <u>XXE</u> EMP- <u>XCK</u> -001											
	Recommended PCB LAYOUT				SERIAL No.							
					KEY POINT							
	2 PIN				PIN CONFIGURATION							
D	KEY POINT											
	CODE	G	A	B	J							
C	GRAPHIC	0°	30°	60°	45°							
												
	PIN CONFIGURATION (Solder Definition)											
B	GRAPHIC											
	2 PIN	3 PIN	4 PIN	5 PIN	6 PIN	7 PIN	8 PIN	10 PIN	14 PIN	16 PIN		
A	UNIT:mm				TITLE FLOS, LB-SER, SIZE 1, PANEL F S/NUT M Pin, PCB S, FRONT			ITEM NO		DRAWN BY Hubert		DATE 2024/03/04
	TOLERANCE ±0.5 mm			SCALE Free		SHEET 2 OF 2		DWG NO FLBC-XXEEMP-XCK-001		CHECKED BY Neo		DATE 2024/03/04
	REV. B		SIZE A4		QC :Inspection Item		CUSTOMER ALTW		APPROVED BY Fred		DATE 2024/03/04	
	1	2	3	4	5	6	7	8 WIO814-03-表單 01A2				

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.