REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	-	2023/12/21	Yunchen	Rev.01 to Rev.A
B	C240471	2024/06/14	Sam Ho	△B X3











Note:
* RoHS Compliant
* QC Important Dimension
* Waterproof rate: IP67, mated
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Extension Nut: Thermoplastic, Black
  Nut: Thermoplastic, Black
  O-Ring: Rubber, Black
* O-Ring: Rubber, Green
* Clamp Ring: Thermoplastic, Black
* Sealing Nut: Thermoplastic, Black
△B * Seal: Rubber, Black, OD:∅4.5mm~∅6.5mm
* One set unassembled in one pe bag



Pin Assignments Front View

M8P-XXBFFB-SR7001

XX: No. Of Pin

UNIT:mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: N SEN, M8 PLASTIC, SCREW CABLE W/O SR, F, F, FI SCREWIN

SCALE 1.5:1 | SIZE A4 | SHEET 1 OF 1

REV. B | WC-REV. .0 | QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Sam Ho	2024/06/14
DWG NO: M8P-XXBFFB-SR7001	CHECKED BY: Aric Ko	DATE: 2024/06/14
CUSTOMER: ALTW	APPROVED BY: Fred Lee	DATE: 2024/06/14

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.