


Note:

- * RoHS Compliant
- *  Important dimension
- * C1
Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
Nut: Metal
Shield: Metal
Outer mold: Thermoplastic, Black
- * C2
Waterproof rate: IP68, mated 1m/24h
IP69K, mated
Housing: Thermoplastic, Black
Pin: Copper alloy, Gold plated
O-Ring: Rubber, Gray
Nut: Metal
Shield: Metal
Outer mold: Thermoplastic, Black
- * Cable: CAT-5E, Shield, 22#*2P+AL/MY+D, OD=6.2mm, PU Jacket, Black
- * Cable length tolerance: $0.5M < L \leq 1M$: $+60/-0$ mm
 $1M < L \leq 3M$: $+120/-0$ mm
 $3M < L \leq 5M$: $+160/-0$ mm
 $5M < L \leq 10M$: ± 100 mm
 $10M < L \leq 20M$: ± 200 mm
 $20M < L \leq 30M$: ± 300 mm
 $30M < L \leq 99M$: ± 500 mm

UNIT:mm				TITLE ACC, SEN, D Code, DB-ENDED MF		<h1>Amphenol LTW</h1> <h2>安費諾亮泰企業股份有限公司</h2>		ITEM NO		DRAWN BY Zhiwei Xie		DATE 2024/03/12					
± 0.5mm				SCALE 1:1				SIZE A4		SHEET 1 OF 1		DWG NO MSDSXXML-SDSFL-SEXXX		CHECKED BY Fisher Wang		DATE 2024/03/12	
				REV. A				WC-REV. A		QC: Inspection item		CUSTOMER ALTW		APPROVED BY Fred		DATE 2024/03/12	