REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2024/01/20	Cherry	Initial Released
B	C240325	2024/03/27	Cherry	△B X2



Pin Out	Pin #	Wire	
		Shield	
	5	--	
	4	Black	黑
	3	Blue	藍
	2	White	白
	1	Brown	棕
C1 & C2			



4P

Pin Assignments Front View

△B MSDSXXML-SDSML-PDXXX

XX: No. Of pin

XXX: 0.5~99 Meters
A05: 0.5 Meters
1:01 Meters
2:02 Meters
:
:
99:99 Meters

Note:
* RoHS Compliant
* QC Important dimension
* Waterproof rate: IP68, mated 1m/24h
* Connector:
  Housing: Thermoplastic, Black
  Pin: Copper alloy, Gold plated
  Nut: Metal
  Shield: Metal
  Outer mold: Thermoplastic, Black
* Cable: UL2517, 22#*4C+AL/MY+B, OD=5.3mm,
  PVC Jacket, Black
△B* Cable length tolerance: 0.5M < L ≦ 1M: +60/-0 mm
  1M <L ≦ 3M:+120/-0 mm
  3 M <L ≦ 5M:+160/-0 mmm
  5 M <L ≦ 10M:±100 mm
  10 M <L ≦ 20M:±200 mm
  20 M <L ≦ 30M:±300 mm
  30 M <L ≦ 99M:±500 mm

UNIT: mm

TOLERANCE

± 0.5mm

TITLE	ACC, SEN, D Code, DB-ENDED MM		
SCALE 1:1	SIZE A4	SHEET 1 OF 1	
REV. B	WC-REV. A	QC: Inspection item	

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY Cherry Huang	DATE 2024/03/27
DWG NO	MSDSXXML-SDSML-PDXXX	CHECKED BY Fisher Wang	DATE 2024/03/27
CUSTOMER	ALTW	APPROVED BY Fred Lee	DATE 2024/03/27

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.