






THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C231272	2023/10/03	Vicky	△B X4




△B ACBD-XXBFFC-LL7XP0  
 XX: No. Of Pin

- S: With Red Color Seal 1, Cable OD 6.0~8.0mm
- M: With Yellow Color Seal 2, Cable OD 8.0~10.0mm
- L: With Blue Color Seal 3, Cable OD 10.0~12.0mm
- A: With Seal 1 & Seal 2 & Seal 3

- △B Note:
- \* RoHS Compliant
  - \* (QC) Important dimension
  - \* Waterproof rate: IP67, mated
  - \* Connector
  - Housing: Thermoplastic, Black
  - Pin: Copper Alloy, Gold plated
  - Nut: Thermoplastic, Black
  - O-Ring 1: Rubber, Gray
  - O-Ring 2: Rubber, Dark gray
  - \* Clamp Ring: Thermoplastic, Black
  - \* Sealing Nut: Thermoplastic, Black
  - \* Seal: Rubber
  - \* One set unassembled in one pe bag

UNIT:mm  
 TOLERANCE  
 ±0.5 mm



TITLE N CERES, ST, C-10A+5A, CABLE W/O SR F, F, CRIMP, 2LOCK △B			
SCALE 8:5	SIZE A4	SHEET 1 OF 1	
REV. B	WC-REV. A.3	(QC): Inspection item	

**Amphenol LTW**  
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Peng	DATE 2018-12-15
DWG NO △B ACBD-XXBFFC-LL7XP0	CHECKED BY Mafei	DATE 2018-12-15
CUSTOMER ALTW	APPROVED BY Jerry	DATE 2018-12-15