






Product Range Overview






Sub-Series Name	Standard	High Density
Mating Style	Screw Thread & Automated Latch	Screw Thread & Automated Latch
Metal Version	✓	✓
No. of Contacts	9, 15, 25, 37, 50*	15, 26, 44, 62*, 78*
Contacts Plating	Gold Plated	Gold Plated
Operating Voltage	125V DC	125V DC
Current Rating	5A	2A
Operating Temperature	Receptacle: -40°C ~ 105°C Overmolded With Cable: -20°C ~ 80°C Field Installable: -40°C ~ 105°C	
Fasten Style	Front	Front
Receptacle	✓	✓
Overmolded Cable	✓	✓
Field Installable	✓	✓
Applicable Wire Gauge	24AWG (0.25mm ²)	26AWG (0.14mm ²)
Mating Cycles	500 Cycles	500 Cycles
IP Rating	Receptacle: IP68 (Unmated, 1M / 24h) Overmolded With Cable / Field Installable: IP67 (Mated)	
Salt Spray Resistant	8h	8h
Vibration Resistant	Frequency range 10~55Hz, Amplitude 1.52mm	
EMI Option	✓	✓
ROHS 2.0 Compliant	✓	✓
REACH Compliant	✓	✓
Accessories	✓	✓

Contact Configuration

Standard D-SUB (5A)

9 Pin			15 Pin			25 Pin			37 Pin		50 Pin*	
												
R	F	C	R	F	C	R	F	C	R	F	R	F

High Density D-SUB (2A)

15 Pin			26 Pin			44 Pin			62 Pin*		78 Pin*	
												
R	F	C	R	F	C	R	F	C	R	F	R	F

R: Receptacle F: Field Installable C: Overmolded With Cable
*Upon Request