




Product Range Overview

Sub-Series Name	M20	M32
Mating Style	Screw Thread	Push Lock With Latch
Plastic Version	✓	✓
No. of Contacts	None, 4	None, 4
Plating of Contacts	Gold Plated	Gold Plated
Current Rating	10A	15A ~ 30A
Operating Temperature	-40°C ~ 105°C	
Field Installable	✓	✓
Applicable Wire Gauge	22 ~ 16AWG (0.34 ~ 1.50mm ²)	16 ~ 10AWG (1.50 ~ 6.00mm ²)
IP Rating	IP67	IP67
UV Resistant	✓	✓
Flammability Rating	UL94V-0	UL94V-0
RoHS 2.0 Compliant	✓	✓
REACH Compliant	✓	✓
Certificates	-	UL6703A

Product Image					
Assembly Type	Non-Assembly	Crimp Type	Non-Assembly	Crimp Type	
Size	M20		M32		
Part Number	CX-00B0M20-7001	CX-04BAM20-7001	CX-00B0M32-700 ^③	CX-04BBM32-7001	CX-04BCM32-700 ^③
① No. of Pins	-	04	-	04	
Current Rating (A)	-	Max. 10A	-	Max. 15A	Max. 30A
② Wire Section	No Terminal	22 ~ 16 AWG (0.34 ~ 1.5mm ²)	No Terminal	16 ~ 14 AWG (1.5 ~ 2.5mm ²)	12 ~ 10 AWG (4.0 ~ 6.0mm ²)
③ Cable O.D.	6.0 ~ 10.0mm		(1) 12.1 ~ 16.0mm (2) 10.1 ~ 12.0mm (3) 8.0 ~ 10.0mm	8.0 ~ 10.0mm	(1) 12.1 ~ 16.0mm (2) 10.1 ~ 12.0mm
Operating Temperature	-40°C ~ 105°C				
Waterproof Rating	IP67				
Accessories Unlock Tool	None		 <p>Part Number: ULT-SSMC-01</p>		

(Unit: mm)